



- RG - 213 TY 50 OHM TGK COAX - MANUFACTURED IN COMPLIANCE WITH MIL-C-17F STANDARDS

MECHANICAL DATA

A	INNER CONDUCTOR	PLAIN COPPER	7 x 0,72 mm
B	DIELECTRIC	LOW DENSITY POLYETHYLENE	ø 7,25 ± 0,18 mm
C	BRAID	PLAIN COPPER	192 x 0,20 mm
		- COVERAGE	98%
D	SHEATH	NON-CONTAMINATING POLYVINYL-CHLORIDE	ø 10,4 ± 0,18 mm
	- COLOUR	BLACK - RAL 9004		
	- PRINTING	## METER ## RG - 213 TY 50 OHM TGK COAX MIL-C-17F CE WEEK/YEAR		

MINIMUM BENDING RADIUS (mm)

- SINGLE	ø EXTERNAL
X 5 - REPEATED	ø EXTERNAL

TEMPERATURE RANGE -30 °C / +70 °C

CABLE WEIGHT (Kg/Km)

- COPPER	84,3
- PLASTIC	
87,2	- TOTAL
171,5	

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE 52 ± 2 Ohm

CAPACITANCE 97 pF/m

VELOCITY RATIO 66%

RESISTANCE

- INNER CONDUCT.	6,2 Ohm/Km
- BRAID SHEATH	4,4 Ohm/Km

TENSION

- SPARK TESTING	5,5 kV
-----------------	--------

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	1,2	
10	MHz	1,8	
50	MHz	4,3	
100	MHz	6,4	
200	MHz	9,5	
400	MHz	13,7	

MAX. POWER RATING W

		dB	W
500	MHz	15,3	
600	MHz	16,9	
800	MHz	20,4	
1000	MHz	23,2	
1350	MHz	28,4	
1500	MHz	30,4	

		dB	W
1750	MHz	33,7	
2150	MHz	38,9	
2250	MHz	39,7	
2500	MHz	42,7	
2750	MHz	45,7	
3000	MHz	48,9	

STRUCTURAL RETURN LOSS dB

30 ÷ 300	MHz	>31	1000 ÷ 2000	MHz	>24
300 ÷ 600	MHz	>28	2000 ÷ 3000	MHz	>22
600 ÷ 1000	MHz	>27 ÷	MHz	-

SCREENING EFFECTIVENESS dB

100 ÷ 900	MHz	>57
900 ÷ 2000	MHz	-
2000 ÷ 3000	MHz	-



- Die obigen Werte entsprechen den Angaben des Herstellers und können nicht garantiert werden.
- Wir behalten uns das Recht vor, Änderungen ohne vorherige Ankündigung vorzunehmen.
- Alle anderen Größen oder andere Ausführungen auf Anfrage

- The above values correspond to the manufacturer's specifications and are not guaranteed.
- We reserve the right to change details without notice.
- Any other sizes or any other designs available on request.